

MINITILT

Motion Sensor

The Teledyne CDL MiniTilt is an OEM, surface or subsea pitch and roll sensor. It provides an accuracy of 0.05 degrees in both axes over the full 360 degree range. The unit can be provided in a surface or subsea (3,000m or 6,000m rated) package or can be supplied in an accurately machined mounting frame for OEM applications.

The MiniTilt is highly compatible with existing pitch and roll sensors. It uses a bank of 6 internal option switches to provide a total of 32 different output data formats.

The zero point can be factory set to any position. This allows for unusual mounting arrangements where the MiniTilt can be placed horizontally rather than vertically. The zero point can be set to any mark on the 360° angle so even offset mounting arrangements can be handled.



PRODUCT FEATURES

- High accuracy (0.05°) low cost
- 3000m depth rated
- 6000m optional
- Full 360 degree range
- Gyro heading input
- 32 data strings options

MINITILT

Motion Sensor

TECHNICAL SPECIFICATIONS

Performance	Data output	RS 232 and current loop
	Baud rate	9600 (other rates available on request)
	Parity	None
8 Pin Connector (Burton or Binder)	1 Vin (5 – 30VDC)	Range 360°
	2 GND	Range 360°
	3 CL Hi (output)	Resolution 0.01°
	4 CL Lo (output)	Accuracy 0.05°
	5 RS 232	Calibration points 128 (per sensor)
	6 RS 232	
	7 CL Hi (gyro input)	
	8 CL Lo (gyro input)	
	Temperature coefficient	0.003°
	Repeatability	0.03°
	Hysteresis	0.05° (average)
	Noise	0.01°
	Frequency response	0.4 seconds (typical)
	Voltage	3 – 50VDC
	Current consumption	<10mA (@12VDC typical)
	Temperature range operating	-30°C to +55°C
	Storage	-30°C to +65°C
	Surface and underwater housing	85mm diameter 104mm high
	Dimensions	Mount details
Weights in air/water		1.15kg/0.55kg
Dimensions (no connector)		104mm x 87mm
Weight of transit case		1.5kg
Dimensions of transit case		240 x 180 x 170mm

COMPANY WITH
MANAGEMENT SYSTEMS
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =

Specifications subject to change without notice.
© 2014 Teledyne CDL, Inc. All rights reserved.



www.teledyne-cdl.com
Email: CDL.info@teledyne.com

Head Office
Silverfield House,
Claymore Drive,
Aberdeen AB25 8GD, UK
Tel: +44 (0) 1224 706655
Fax: +44 (0) 1224 709840

Houston
10661 Shadow Wood Drive,
Houston, Texas 77043, USA
Tel: +1 281 710 7276
Fax: +1 281 712 1757