

SeaBat 8101

Multibeam Echosounder




- Phase and amplitude bottom detection
- 150° swath coverage (upgradeable to 210°)
- 240kHz frequency
- Up to 600m swath width

The SeaBat 8101 Multibeam Echosounder measures discrete depths, enabling complex underwater features to be mapped with precision. Dense coverage is achieved utilizing up to 4,000 soundings per second for a swath up to 600 meters in width, even as the survey vessel travels at speeds in excess of 12 knots.

With high accuracy and a measurement rate of up to 40 profiles per second, the SeaBat 8101 enables surveys to be completed faster and in greater detail than previously realized.

The SeaBat 8101 transducer is available for operating depths of 120, 300, 1500, and 3,000 meters. Small and lightweight, it can be mounted on underwater vehicles (ROV or towed) and transported to locations where accurate measurements are required.





SeaBat 8101

Multibeam Echosounder

SYSTEM PERFORMANCE

Operating Frequency:	240kHz (nominal)	
Swath Coverage:	150°	(upgradeable to 210°)
Max Range:	300m	450m max range available with ER option
Number of Beams:	101, beamspacing 1.5°	
Along-Track Beamwidth:	1.5° (nominal)	
Across-Track Beamwidth:	1.5° (nominal)	
Max. Update Rate:	40	
Operational Speed:	Up to 18 knots	

PROCESSOR SPECIFICATIONS

Power Required:	100/240VAC, 47/63Hz, 100W maximum	
Data Uplink:	High-speed digital coax with fiber-optic option	
Computer Interface:	10MB Ethernet and RS232C	
Data Downlink:	Serial, 19.2k baud	
Display Video Out:	SVGA: 800 x 600;	Refresh Rate: ~72Hz
Graphics Colors:	Sonar Image:	256 Colors
	Other Graphics:	8-bit RGB
Input Device:	3-Button Trackball	
Dimensions (HWD):	177 x 483 x 417mm	
Mounting:	19in. rack mountable	
Temperature:	Operating:	0° to +40°C
	Storage:	-30° to +55°C
Weight:	20kg (44 lbs.)	

DISPLAY SPECIFICATIONS

Screen Size:	14" diagonal
Display:	SVGA High-Resolution, Color Monitor
Power Consumption:	80W
Weight:	11.2kg (24.6lbs.)



SONARHEAD SPECIFICATIONS

Power Requirements:	24VDC, 2 amps max. (Power available from Processor.)	
Operating Depth:	120m (300,1500, and 3000m available)	
Dimensions:	266 x 320mm (W / D) excluding projector	
Temperature:	Operating:	-5° to +40°C
	Storage:	-30° to +55°C
Weight (aluminum):	Dry:	26.8kg (59lbs.)
	Wet:	4.8kg (10.6lbs.)
Weight (titanium):	Dry:	40kg (88lbs.)
	Wet:	18kg (39.6lbs.)

OPTIONS

Sidescan upgrade	Mounting plate assembly
Fairings	Spares kit
Titanium housing	210° swath
Extended-Range (ER) projector	Coax to fiber optic interface unit
Increase sonar head depth rating	

RESON reserves the right to change specifications without notice. © 2006 RESON A/S
For Acoustical Measurement Accuracy please refer to www.reson.com or contact sales.



RESON A/S
Denmark
Tel: +45 4738 0022
E-mail: reson@reson.dk

RESON GmbH
Germany
Tel: +49 431 720 7180
E-mail: reson@reson-gmbh.de

RESON Inc.
USA
Tel: +1 805 964-6260
E-mail: sales@reson.com

RESON B.V.
The Netherlands
Tel: +31 (0)10 245 1500
E-mail: info@reson.nl

RESON Offshore Ltd.
United Kingdom
Tel: +44 1224 709 900
E-mail: sales@reson.co.uk