

# TideMaster



TideMaster has been designed to provide an accurate, versatile and easily deployed tide gauge for use in short or long term survey operations with either pressure or radar sensor measurement. Optional control/display panel, Bluetooth, SD card memory and optional weather sensor provide unrivalled functionality. Low power consumption and user selectable sampling regime allow for up to a year of autonomous operation, whilst optional telemetry packages extend the capabilities for real time operations. TideMaster is compatible with a wide range of hydrographic software and tools.

## Specifications

<b>Product</b>	TideMaster
<b>Country of origin</b>	UK
<b>Manufacturer</b>	Valeport Limited

## Pressure transducer option

<b>Type</b>	Vented strain gauge, with stainless steel mounting bracket.
<b>Range</b>	Standard 10dBar (approx 10m), with 20m cable. Other ranges and lengths available.
<b>Accuracy</b>	±0.1% Full Scale.
<b>Calibration</b>	Held within logging unit.
<b>Dimensions</b>	18mm diameter x 80mm.

## Radar level sensor option

<b>Minimum Range</b>	0.8 m
<b>Maximum Range</b>	20 m
<b>Beam Angle</b>	±6°
<b>Frequency</b>	25 GHz
<b>Accuracy</b>	±10 mm
<b>Precision</b>	1 mm
<b>Footprint</b>	Radius at different ranges

Range [M]	Radius [M]
2	0.21
5	0.53
10	1.05
20	2.10
35	3.68

## Weather sensor options

### Windsonic ultrasonic anemometer

<b>Wind speed</b>	0-60m/s
<b>Wind direction</b>	0-359°
<b>Calibration</b>	Held within sensor.
<b>Dimensions</b>	142mm x 160mm.

## Radio Telemetry

<b>Frequency</b>	Selectable frequency UHF synthesized radio transceiver, (458.5 - 458.9 MHz).
------------------	--

## Software

System is supplied with TideMaster Express Windows based PC software, for instrument setup, data extraction and display.

## MetPak II™ Weather Station

<b>Wind speed</b>	0-60m/s
<b>Wind direction</b>	0-359°
<b>Air temperature</b>	-35°C to +70°C
<b>Relative humidity</b>	0 – 100% RH
<b>Barometric press</b>	600 – 1100hPa/mbar
<b>Dew point</b>	As per temperature range
<b>Calibration</b>	Held within sensor.
<b>Dimensions</b>	142mm x 274mm.

## Logging unit

<b>Housing</b>	Injection moulded housing rated to IP67, with injection moulded mounting bracket.
<b>Display</b>	Optional control/display (128x64 OLED) panel for system configuration and data display
<b>Power</b>	4 "C" cells within separate sealed compartment. Tool-less battery change. Alkaline cells provide power for up to a year of autonomous sampling
<b>Memory</b>	512 MB SD card memory allowing for effectively unlimited data storage.
<b>Sampling</b>	Raw data sampled at 8Hz, mean and standard deviation of burst samples is logged. 5 pre-programmed burst modes + custom sampling mode. Continuous Sampling Mode (1Hz)
<b>Switching</b>	Power switch on unit
<b>Resolution</b>	Data logged to 1mm resolution.
<b>Comms</b>	Integral Bluetooth for short range wireless communication RS232/RS485 for cabled communication
<b>Dimensions</b>	Housing 52 mm x 144.5 mm x 197 mm. Bracket 35 mm x 210 mm x 159 mm. Mounted 61.5mm x 210 mm x 197 mm
<b>Weight</b>	1.1 kg (approx) including batteries.

## Ordering

<b>0741001</b>	TideMaster portable water level recorder. c/w wall mounting bracket and electronics/logger (with display) in rugged injection moulded housing with batteries. Supplied with Windows based TideMaster Express software and operating manual. (Transducer option below required)
<b>0741002</b>	TideMaster portable water level recorder c/w wall mounting bracket, electronics/logger (without display) in rugged injection moulded housing with batteries. Supplied with Windows based TideMaster Express software and operating manual. (Transducer option below required)
<b>0741PT1D20</b>	1 bar transducer c/w 20m cable and connector.
<b>0745001</b>	VRS-20 Radar level sensor with mounting bracket, 5m power/data cable, junction box, software, manual and transit box