

DVL1000

4000 m



Bottom-track from over 0.2 to 75 m range; 4000 m max. operational depth

The DVL1000 is the world's smallest commercially available Doppler Velocity Log. It combines compact design with unprecedented functionality, being able to fly higher in the water column and closer to the seabed than similar equipment. It has a maximum operational depth of 4000 m and is ideally suited for subsea navigation where size and weight are a concern. This 1 MHz Doppler Velocity Log is used by industry leaders in the subsea market because of its high accuracy and state-of-the-art technology.

Specifications

Product	DVL 1000 4000m
Country of origin	Norway
Manufacturer	Nortek
Material standard models	POM and titanium housing

Highlights

- Industry's smallest DVL
- Bottom track from 0.2-75 m range
- Quality estimates - per beam and ping

Applications

- Observation-class ROVs and AUVs
- Near-bottom operations
- Highly accurate subsea surveys
- Easy integration with high-grade INS

Bottom velocity

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	± 0.1% / ± 0.1 cm/s
Minimum altitude	0.2 m
Maximum altitude	75 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

Water tracking

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Minimum range	2.0 m

Current profiling

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity resolution	0.1 cm/s
Interval	User-specified Nth ping
Maximum range	30 m
Blanking	0.1 m
Cell size	0.2-2.0 m
Max # cells	150

Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C

Mechanical

Depth rating	4000 m
Weight	2.7 kg
Weight in water	1.7 kg
Height	164 mm
Diameter	ø114 mm

Hardware

Frequency of operation	1 MHz
Configuration	4-beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional

Interfaces

Serial (either serial or ethernet)	Configurable RS232 or RS422 Subconn connector, 8-pin male
Ethernet	10/100 Mbits Auto MDI-X.TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client /Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping.Multiple simultaneous data format transmission possible
Data formats	Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, Variants of PDx
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (Ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)

Sensors

Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

Power

DC input	12-48 V
Maximum peak current	1.5 A
Average power	1.3 W