

RQ-001 - 17" Subsea Rotary Cutter



Key Features:

- ROV deployable
- Light weight
- Self-clamping
- Different sizes of blade options
- Easy to operate
- Cuts a variety of materials

WHATS INCLUDED

17" Rotary Cutter.
Operational Hose Kit.
Certification Pack.
Blades (consumable).

OPTIONS

Buoyancy Blocks.

Spares Kit (included with rental).

Fight Case.

Customisation – we can customise any tool.

Description

The 17" Rotary Cutter uses strong Steel jaws to securely clamp on to various structures and cut material from a minimum of 10 inches and up to a maximum of 17 inches in diameter (Slight tool modifications can be conducted for larger cuts).

The jaws are actuated by two hydraulic rams and are adjustable over three different position depending on the diameter of cut. These ensure that the cutter clamps onto and centralises the material being cut. There is a bolt-on guide to aid the cutting of 10" - 14" material. The main body of the cutter is made up from lightweight aluminum. The motor is mounted on a slide to extend and retract the blade position.

The blade itself is stainless steel, tungsten carbide tipped. This means it can easily cut ferrous and non-ferrous metals as well as high-tensile steels with ease. A counterbalance valve is set to stop the weight of the motor and blade from dropping if hydraulic pressure is removed.

A variety of blade sizes and types can be mounted onto the blade hub, making this cutter not only light and simple to deploy but highly versatile.

Web: www.aleron-group.com Email: info@aleron-group.com Tel: +44 (0) 1330 861704





RQ-001 - 17" Subsea Rotary Cutter

Overall Specifications	
Cut Distance 2	255mm to 406mm (10" to 16")
Max Blade Diameter 1	1000mm (39")
Minimum Clamp Diameter 4	450mm (18")
N	Note: Packers can be used for smaller cuts
Max Intermitting Speed 2	240 RPM
Main Motor	
Pressure 1	140 to 180 Bar (2600 PSI)
Flow 2	25 to 50L/Min
Jaw Clamp	
Pressure 5	50 to 100 Bar (1500 PSI)
Flow 1	1 to 5L/Min
Blade Extend	
Pressure 2	20 to 100 Bar (1500 PSI)
Flow	0.1L/Min
Weights and Dimensions	
Weight in Air 1	100kgs
Weight in Water 7	70kgs (can be reduced with Buoyancy)
Dimensions L	L1732 x W1000 x H434mm

Picture above shows a test cut of 240mm multi layered armored umbilical

WHATS INCLUDED

17" Rotary Cutter.
Operational Hose Kit.
Certification Pack.
Blades (consumable).

OPTIONS

Buoyancy Blocks.
Spares Kit (included with rental).

Fight Case.

Customisation – we can customise any tool.

Web: www.aleron-group.com Email: info@aleron-group.com Tel: +44 (0) 1330 861704

