

# RTS RS232 Splitter



One to four, RS232 distribution box - Now with USB and RS422 option

RS232 splitter for distribution of sensor signal to multiple computers. Simplifies setups and make a well arranged interconnection between computers and sensors. No more unpredictable RS232 signals caused by serial ports connected in parallel. A special duplex output connector, CH1/CH2, makes it easy to do sensor configurations without any bypasses or disconnections.

## Specifications

|                   |                                 |
|-------------------|---------------------------------|
| Product           | RTS RS232 Splitter              |
| Country of origin | Norway                          |
| Manufacturer      | Rental Technology & Services AS |

RTS – Rental Technology & Services

[rts.as](http://rts.as)

**rts**

Åkrehamn, Norway tel: +47 52 81 47 60 [sales@rts.as](mailto:sales@rts.as) Bridge of Don, Aberdeen, UK tel: +44 (0) 1224 907530 [sales.uk@rts.as](mailto:sales.uk@rts.as)

## Main features

- RS422 to RS232/USB converter
- RS232 to USB converter
- Baudrate up to 230 kbps
- Duplex port
- ESD protected inputs
- 1000V magnetic isolation
- Small size

## Technical specifications

|                   |                     |
|-------------------|---------------------|
| <b>Power</b>      | 5V DC Supply or USB |
| <b>Dimensions</b> | 169mm x 44mm x 83mm |

## Connections

|               |  |
|---------------|--|
| <b>Input</b>  | 1 x RS232 or RS422 / 9 pin D-Sub                               |
| <b>Output</b> | 4 x RS232 / 9 pin D-Sub<br>1 x USB (Distribute only Rx and TX) |

## Environmental

|                              |                    |
|------------------------------|--------------------|
| <b>Operating temperature</b> | 0 to +55°C         |
| <b>Weight</b>                | 0,4 kg             |
| <b>Housing</b>               | Anodized Aluminium |