

Wideband® Sub-Mini 6+ Transponder/Responder



The Wideband® Sub-Mini 6+ (WSM 6+) is Sonardyne's latest generation of versatile Ultra-Short BaseLine (USBL) transponders/responders that support Wideband 2 signals. The WSM 6+ is designed for positioning Remotely Operated Vehicles (ROVs), towfish and other mobile targets in water depths up to 4,000 m. The unit is compatible with USBL systems, including Sonardyne's Wideband 2, and has an internal Li-ion battery for emergency transponder mode. Featuring an omni-directional transducer and supporting internal sensors, it's lightweight, rugged, and integrates with Sonardyne's modem and logging equipment.

The compact and rugged design is based on the field proven WSM mechanics and is available in Medium Frequency (MF) directional and MF omni-directional versions. The latest Sonardyne Wideband 2 signal technology has been incorporated, which offers superior ranging accuracy and fast USBL position updates.

Specifications

Product	Wideband® Sub-Mini 6+
Country of origin	UK
Manufacturer	Sonardyne International Ltd

The WSM 6+ improves on its predecessors by offering full two-way Wideband support – Interrogation and reply signals. All Wideband 2 and Wideband 2+ signals are supported. Legacy support is also available for Wideband 1 and HPR 400. The configuration is programmable using supplied software and a serial link or it can be configured acoustically via iWAND.

This allows the WSM 6+ to be configured for use with all of the popular MF frequency acoustic navigation systems

The Type 8370-1111 WSM 6+ is equipped with an omni-directional transducer and is depth rated to 1,000 m making it suitable for a wide range of general USBL tracking applications.

The Type 8370-4112 WSM 6+ is a 4,000 m rated unit and features a higher power directional transducer. Both types of WSM 6+ have a depth sensor fitted as standard to aid USBL positioning accuracy and an external on/off switch to save the battery when not in use.

WSM 6+ variants are available with acoustically controlled output lines suitable for external motor drive, burn-wire or contact closure releases.

Key features

- Choice of omni-directional or directional beam-shape
- Choice of 1,000 or 4,000 m depth rating
- Sonardyne Wideband 1 and HPR 400 navigation compatible
- More than 500 unique Sonardyne Wideband 1 and 2 addresses
- Full two-way Sonardyne Wideband 2 interrogation and reply Mitigates interference and multi-path issues
- Transponder or responder operating modes
- Rechargeable NiMH battery
- Compact and rugged design
- Release variants available
- Depth sensor for improved USBL positioning performance

Specifications

Feature		Type 8370-1111	Type 8370-4112
Depth rating		1,000 m	4,000 m
Transceiver beam shape		Omni-directional	Directional
Transmit source level (dB re. 1 µPa @ 1 m)	External power	187 dB	196 dB
	Battery	184 dB	193 dB
Tone equivalent energy (TEE) ¹ (external power)		193 dB	202 dB
Receive sensitivity (dB re 1 µPa)		<85 dB	<80 dB
Power supply		Rechargeable NiMH battery or external.	202 dB
Operating channels		All Sonardyne Wideband	HPR 400 channels
Depth sensor		±0.5% full scale (100 bar)	±0.5% full scale (400 bar)
Operating life		>6 days	>3 days
Update rate (maximum)		>2 Hz	>2 Hz
Quiescent life (battery)		>35 days	>35 days
Connector	5-way (standard)	Subconn MCBH5M	Subconn MCBH5M
	8-way (burnwire/motor release)	Subconn MCBH8F	Subconn MCBH8F
Operating temperature		-5 to 40°C	-5 to 40°C
Storage temperature		-20 to 55°C	-20 to 55°C
Mechanical construction		Anodised aluminium alloy	Anodised aluminium alloy
Dimensions (length x diameter)		420 x 75 mm	429 x 96.5 mm
Weight in air/water		3.2/1.3 kg	5.5/3.2 kg
Battery charger		8370-011-01	8370-011-01
Operational frequency		MF (20–34 kHz)	MF (20–34 kHz)

