

ROV-BASED

PASSIVE ACOUSTIC LEAK DETECTOR

LEAKlog® PA1

Enhancing subsea pipeline integrity through advanced acoustic sensing, Aquatec's LEAKlog® PA1 Passive Acoustic Leak Detector excels in pinpointing high-pressure gas and liquid leaks. Optimised for deep-sea operations up to 2,000 m, this instrument harnesses ultrasonic technology to detect the distinct acoustic signatures of leaks in the 30-150 kHz frequency range.

With remarkable precision, the LEAKlog® PA1's highly sensitive directional hydrophone and sophisticated noise filtration capabilities isolate leak sounds from ambient underwater disturbances. Seamlessly integrating with ROVs and Aquatec's AQUAtalk™ software, it delivers real-time acoustic data to operators, enabling rapid leak localisation. An invaluable addition to multi-sensor leak detection strategies, the LEAKlog® PA1 ensures comprehensive pipeline monitoring where conventional methods fall short.



KEY FEATURES

- Advanced ultrasonic acoustic sensing tuned to detect leak signatures in the 30-150 kHz range
- Highly directional hydrophone for precise leak localisation
- Sophisticated noise filtration to isolate leak sounds from ambient underwater noise
- Selectable gain options and auto-gain for optimised sensitivity in varying conditions
- Real-time data Integration with AQUAtalk™ software for immediate leak analysis

APPLICATIONS

- Deep-sea pipeline integrity monitoring for the Oil & Gas industry
- Rapid localisation and mitigation of high-pressure gas and liquid leaks
- Complementary technology for multi-sensor leak detection strategies
- Preventive maintenance and routine subsea inspection surveys
- Remote subsea acoustic monitoring for various underwater operations including valve monitoring

SPECIFICATIONS

Depth Rating	2,000 m
Frequency Response	From 30kHz to 150kHz
Gain Options	40dB, 52dB, 60dB and 72dB
Supply Voltage	12 Vdc
Output	0-5 V
Dimensions	80 mm (3.15 in) diameter × 261 mm (10.28 in) length
Weight	1.4 kg (3.08 lbs)
Material	Acetal and ABS

ACOUSTIC LEAK DETECTION

The LEAKlog[®] PA1 offers unparalleled acoustic precision. This method utilises a directional hydrophone that 'listens' for high-frequency sounds produced by pressurised fluids escaping through small orifices. By using precision filtering, the LEAKlog[®] PA1 discerns the distinct ultrasonic frequencies of a leak amidst the sea of underwater sounds, including those from ROVs and surface vessels.

The advanced acoustic detection capability of the PA1, powered by noise filters, zeroes in on leaks across a spectrum of pipeline and equipment failures – from risers and flanges to complex sub-sea control systems. Designed for versatility, the hydrophone can be deployed via ROV, AUV, or towed vehicles, providing flexibility and rapid pinpointing of leak locations. Embracing the latest in data handling, the PA1 ensures that leak detection remains accurate and efficient even amid the bustling activity of marine operations.



LEAKlog[®] is a registered trademark of Aquatec Group Limited. All other trademarks & registered trademarks are acknowledged. Aquatec Group Limited reserves the right to make changes to the specifications contained in this document without notice in the interests of maintaining or improving product quality. Document ©2024 copyright Aquatec Group Limited. Nov 5 - V3.2

Aquatec Group Ltd.

Aquatec House, Stroudley Road, Basingstoke RG24 8FW, UK | aquatecgroup.com | inquiry@aquatecgroup.com | +44 (0) 1256 416010