

Triton® R.O.V. Hook



It is of paramount importance that a remote operated hook for sub-sea use is safe and dependable. The Triton® R.O.V. Hook series was designed with these specific criteria in mind.

Specifications

Product	Triton® R.O.V. Hook
Country of origin	UK
Manufacturer	COSALT

Key features

- Safety latch can be locked in a closed position.
- Eye designed to correspond with shackles
- RR-C-271 U.S. Federal specification.
- Ergonomic entry guide tip.
- Made of Stainless Steel 2324.
- One-piece construction for safety.
- Proper snag-free design with hexagonal long shank.
- Ergonomic safety latch with stainless release wire.

Specifications

WILL	8.5T	12T	25T	35T
A	31 mm	37 mm	51 mm	51 mm
B	78 mm	93 mm	140 mm	140 mm
C	36 mm	44 mm	78 mm	78 mm
D	57 mm	70 mm	119 mm	119 mm
E	57 mm	51 mm	119 mm	119 mm
F	50 mm	61 mm	90 mm	90 mm
G	72 mm	64 mm	128 mm	128 mm
H	40 mm	45 mm	70 mm	70 mm
I	72 mm	48 mm	80 mm	80 mm
L	438 mm	527 mm	736 mm	736 mm
Weight	9 kg	13 kg	46 kg	46 kg

