

ROV SHANK HOOK HK5



The ROV Shank Hook Type HK5 is an easy and cost-efficient solution for small and basic subsea lifting operations. The long hexagonal body makes it easy to handle by ROV manipulators and can be opened remotely by pulling the retraction wire. The hooks are delivered with the following WLL from 5Te to 400Te, 4:1 in safety factor. Hooks are used in towing, mooring and lifting systems as a connection between slings, rope, wire rope and chain. ROV type hooks are modified for easy ROV handling during hook-up or release. Eye hooks HK2 are generally used for lifting systems.

Specifications

Product	Syclone 3 Torque Tool
Country of origin	Netherlands
Manufacturer	GN Rope Fittings

Specifications

Material	Alloy steel
Safety factor	4 times
Finish	Painted
Temperature range	-40°C up to +200°C, Polar Rated
Standard certification	Certificate of Conformity 3.1 material certificate EN 102043.1 material certificate EN 10204 Fittings

Specifications

Art. No	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	P ton	Weight kg
53000100	100	140	175	472	150	831	110	100	228	120	120	240	4.75	178
53000125	125	145	180	509	170	890	124	110	260	140	140	240	4.75	249
53000160	160	157	190	614	190	953	138	135	300	160	150	250	6.5	362
53000200	200	176	224	688	230	998	148	135	350	175	150	250	8.5	496
53000250	250	194	250	780	256	1063	175	145	370	200	160	250	8.5	671
53000300	300	210	280	755	255	1153	190	155	360	220	170	300	9.5	790
53000400	400	234	315	855	305	1253	210	185	420	240	190	300	9.5	1064

