

# AQUAswitch™



Engineered for both shallow and deep aquatic environments, the AQUAswitch™ offers a user-friendly interface, allowing seamless integration with a variety of subsea instruments and systems. This feature ensures the secure activation and deactivation of your equipment at any stage of deployment, enhancing operational flexibility and reliability

## Specifications

<b>Product</b>	AQUAswitch™
<b>Country of origin</b>	UK
<b>Manufacturer</b>	Aquatec Group Ltd.

## Key features

- Designed for ROVs and divers
- Robust and durable
- User-changeable switch configuration
- Positive detents in on/off positions
- Custom position labels available
- No power needed to operate
- 5 Amps continuous, 3 Amps switching
- 255 VDC (300 VAC)
- 120 Watts total load
- Ideal for integrations in systems

## Specification

<b>Maximum voltage rating</b>	255 VDC (300 VAC) (600VAC/DC available)
<b>Maximum current rating</b>	5 AC/DC continuous, 3 AC/DC switching
<b>Maximum power</b>	120 Watts total load
<b>Connector</b>	MCBH2M
<b>Switch configurator</b>	Normally Open/Normally closed contact (User changeable)
<b>Attachments</b>	3 mounting holes Ø15 PCD M6 x 8 dp max
<b>Maximum depth</b>	6,000 m
<b>Material</b>	316 Stainless Steel
<b>Weight</b>	4.25 kg
<b>Dimensions</b>	180 mm diameter x 98 mm (excluding connector)

## Custom position labels



## Rugged and compact

